

High-Speed Dual-Sided Smart Card Printer with Elevator

By NBS Technologies

ImageMaster™ E-40

Desktop Production Printer
with 10 station
Smart Card Elevator



HIGH-SPEED DUAL-SIDED SMART CARD PRINTER WITH FEATURES & PERFORMANCE THAT PERFORMS WELL IN THE MOST DEMANDING ENVIRONMENTS

THE IMAGEMASTER™ E-40 OFFERS THESE KEY FEATURES AND BENEFITS:



COMPACT AND FLEXIBLE

- Delivers fast monochrome printing: up to 4000 cph single-sided & 1500 cph dual-sided
- Programmable card cleaning to help maintain quality
- Can operate as a stand-alone unit with keyboard



NETWORK AND ENCODING

- **Up to 10 Contact stations, up to 5 of which can also support Contactless Smart Card**
- Supports Ethernet and Serial connectivity
- Options for magnetic encoding Contact, Contactless or both



EASY-TO-USE

- 500 card input hopper & output stacker
- LCD screen displays printer status and diagnostics
- Easy to change ribbon and thermal print head
- Clear card support is standard
- Works in line with our **NBS-1500 Mailing System**



Printer Specifications

Single/Dual-sided	Fast, monochrome printing single-sided and double-sided printing
Print method	Thermal transfer (mono)
Card encoding options	Magnetic encoding: 3 track, Dual Coercivity, ISO 7811, Bit to Bit (binary); JISA, JISC and JISA/ISO in single pass
Smart Card Elevator Options	Configurable up to 10 Contact smart card stations, up to 5 of which can also support contactless personalization (Contact Station: ISO 7816 Part 1-3 T=0, T=1, Class A&B (5V and 3V) compliant, (Contactless: ISO14443 Part 1-4 A/B Mifare Classic/Desire/ICAO T=CL up to 848kbps and Felica
Warranty	12 month
Printer interfaces	Two-line, 40-character LCD Keyboard for manual data entry, RS-232C Serial 9 Pin; Ethernet 10/100bT, TCP/IP printing using LPR/LPD or Raw socket
Software drivers	Supports online printing from a variety of host computers including PC running Microsoft Windows 7, 8, 10, and AS-400 Supports both internally generated layouts using ASCII text fields from host computer, or full Microsoft Windows® compatibility with Windows 7, 8, and 10. Supported by NBS SmartSys™ Tabletop batch issuance software, a user-friendly, Windows card design and production application, ideal for batch issuance.
Fonts/Images	300 dots per inch (11.8 dots per mm) resolution. Full range of monochrome color ribbons (full and half widths) available. Shipped with Swiss Regular: 6, 8, 10, 14, 18, 24 pt, Swiss Italics: 6, 8, 10, 14 pt, OCRA: 10, 12 pt, Dutch Bold: 6, 8, 10, 18, 24 pt, Any True-Type font can be downloaded from Microsoft Windows to support customized fonts PC Dash Board software for use in downloading additional fonts and images also used for flash loading of firmware for easy updates. It also can be used to back the machine settings.
Barcodes	EAN 13 & 8, UPC-A, Code 39, Codabar, Code 128, Code 12 of 5. When utilizing Smartsys you can also produce QR codes & PDF417
Card capacity	500 input hopper and output stacker, 25 - reject tray, Two production counters, one re-settable In-line mailer interface option is available
Weight	118lbs (53.5kgs)
Power source	110-230 Volts, 50-60 Hz FCC Class B, CE, ETL and ROHS compliant
Dimensions	14.5" (368mm) D x 24" (610mm) W x 35.75" (908mm) H
Environment	Operating temperature: 15°C to 30°C, Relative humidity: 20% to 65% non-condensing, Storage temperature: -5°C to 70°C, Storage humidity: 20% to 70% non-condensing, Ventilation: Free air
Monochrome Print speed	Single-sided: Up to 4000 cards per hour, Dual-sided: Up to 1500 cards per hour
Maintenance	Automatic card cleaning mechanism with user configurable cleaning

Card Specifications

Types	PVC & composite PVC - including breakaway and key cards
Maximum print area	0.100" +/- 0.010" from side edges of card
Card width/length	ISO CR-80-ISO 7810: 53.98mm (W) x 85.60mm (L) / 3.375" x 2.125"
Card thickness	0.024" (0.61 mm) to 0.030" (0.76mm) . (Optional)Thin card kit for 0.015" (0.38mm) and 0.020" (0.51 mm) cards



The ImageMaster E-40 works in line with our NBS-1500 Mailing System to create a **low-cost** issuance & fulfilment system.



Contact our NBS card personalization experts for full details on this and other card personalization products at:

Global Headquarters
10925 Bren Road E
Minneapolis, MN 55343
USA
tel: +1 952.912.9400
fax: +1 952.912.9439
email: info@nbstech.com

B1 Moorfield Point
Slyfield Industrial Park
Guildford, Surrey GU1 1RU
United Kingdom
tel: +44 (0)1483 563200
fax: +44 (0)1483 511189
email: javelin@nbstech.com

20614 Eastleigh Crescent
Langley BC V3A 4C4
Canada
tel: +1 604.530.6012
fax: +1 604.530.9685
email: info@nbstech.com

